

BASKETBALL HOIST

EQUIPMENT LIFTING | BASKETBALL HOIST

PRODUCT OF FRANCE
MANUFACTURED IN FRANCE

The electric basketball hoist safely raises and lowers ceiling-suspended basketball backboards in sports halls and gyms. CE certified.

Single-phase (1~), it operates with a 230 V, 50 Hz motor power supply and has a lifting capacity of 300 kg.

Specially designed for increasingly heavier retractable, ceiling-suspended basketball hoops, it provides the powerful drive system required to operate them.



COMFORT

- 2 versions: with or without emergency descent, allowing manual lowering in the event of a power failure
- Quick connection without opening the electrical control box, thanks to an integrated connector and plug
- (optional) Radio remote control for remotely raising and lowering the basketball backboards.

STANDARD INCLUDED EQUIPMENT



Key-operated wall control box with 2m integrated cable (pendant control extensions also available)



6-pin connector for a quick pendant control connection



Power plug with 0,5 m cable (power cable extensions also available)



SAFETY

- Motor with thermal protection against overheating
- Key-operated wall control box with 2m integrated cable and emergency stop for increased safety
- Upper and lower limit switches
- Designed in accordance with EN 14492
- (optional) Protective cover for the revolution counter

ACCESSORIES

300209



Ø6,3mm steel wire-rope

15m: 540134
30m: 540136



Pendant control extension (up to 200 m)

461025



Wireless remote control with IP65 rated double insulation and 100m reach*
* used outdoors without interference

540205



Protective cover with fixing screws



Technical Features	Basketball hoist	
	Without emergency descent Type 180A Sales code 540122	With emergency descent Type 180B Sales code 540123
Working Load Limit - WLL	300 kg	
Phase and Tension	1~ 220-240V	
Frequency	50 Hz	
Weight	31 kg	37 kg
Operating speed	7 m/min	
Rated/Nom. current	7 A	
Motor Power	0,75 kW	
Dimensions	770x430x320 mm	750x490x320 mm
Ø and type of wire rope	Ø6,3 mm - 7x7x0,7 acero galvanizado	
Maximum lifting length	7 m of wire rope (32 revolutions)	
Upper and lower limit switch	Yes	
Manual emergency descent	No	Yes
Operating temperature	-10°C/ +55°C*	

* Protected from the elements and stored in a clean, dry place

FIXATOR

8 Rue du Bois Rinier, 49181, Saint-Barthélemy d'Anjou, France
T. 0033 (0)241 31 17 00 Email : info@fixator.com

www.fixator.fr/en

FIXATOR
SAFETY AT THE VERY TOP

MANUFACTURER OF HEIGHT ACCESS SOLUTIONS SINCE 1924