

# MANUAL HOIST CRANK GEAR

PRODUCT OF FRANCE  
MANUFACTURED IN FRANCE

I TEMPORARY PERSONNEL LIFTING | Manual crank hoist



## COMFORT

- ✓ Five models available with a maximum load capacity ranging from 60 to 300 kg
- ✓ Easy maintenance, 1 annual inspection
- ✓ Detachable crank handle
- ✓ Robust and anti-corrosive - galvanized steel finish



## SAFETY

- ✓ Equipped with an automatic brake
- ✓ Automatically irreversible in both directions of rotation
- ✓ Ratchet free

The geared crank manual hoist is commonly used in sports halls for manual lifting of basketball boards and handling of awnings. Its maximum load capacity ranges from 60 to 300 kg.

### TECHNICAL SPECIFICATION

Description	3060	3120	3121	3200	3300
Rated load (kg)	60	120	300	200	300
Force on first layer (kg)	100	200	500	300	500
Force on last layer (kg)	60	120	300	200	300
Weight (kg)	6,6	7,1	8	7,1	8,2
Gear Ratio Coefficient	1,8	4,1	4,1	6,1	10,2
Average lift per crank revolution (mm)	160	70	60	50	30

### WINDING CAPACITY

Description	3060	3120	3121	3200	3300
Cable Ø 3,15 mm	52 m	52 m	-	-	-
Cable Ø 4 mm	32 m	32 m	-	-	-
Cable Ø 4,5 mm	25 m	25 m	29 m	20 m	20 m
Cable Ø 5 mm	20 m	20 m	-	16 m	16 m
Cable Ø 5,4 mm	17 m	17 m	-	14 m	14 m
Cable Ø 6,3 mm	13 m	13 m	-	10 m	10 m

