



UPS2T Pulley (Universal Pin-Safe)



I PERSONNEL AND MATERIAL LIFTING | LIFTING PULLEYS

The UPS2T is an **opening** universal pulley with double locking axis and other innovative security features. Its capacity is 2 tons.

It allows reeving  (thus doubling the lifting capacity of the winch) or wire rope diversion  using the Fixator Liftho or Motrix winches (or any other cable hoists of similar capacities).



- ✓ Designed according to F EN 1808 regulation
- ✓ ISO:9001 compliant



For installation work in elevator shafts or other lifting needs up to 2 tons.

Capacity: 4400 lbs (2 tons)
Weight (without hook): 9 lbs (4.1 kg)
Ø groove: 8" (200 mm)

Dimensions: 11"x13"x3" (280x325x83 mm)
Cable: Torsion resistant Ø 21/64" (8.3mm), 3/8" (9.5mm) or 13/32" (10.3mm)

CHOICE OF HOOKS: Fixed or semi-rotating



ADJUSTABLE SIDE PADS:

Avoid disorgement and allow to reach a deflection angle up to 90°



CHOICE OF WIRE-ROPE:

Rotation-resistant, available in different diameters: 8.3, 9.5 or 10.3mm



LOCKABLE AND REMOVABLE AXIS:

Removable and double locking axis thanks to a safety pin allowing easy insertion of the cable or hookless use



COMPATIBLE HOISTS:

Fixator hoists (CE standard):
 Liftho 600/800/1000
 Motrix 750/1000
 Fixator hoists (UL/CSA standard):
 e.lift 1000/1500/2200 lbs
 (or wire-rope hoists with lifting capacity up to 1T)

